Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2017

Supplier's name or trade mark: ASKO

Supplier's address: Sockerbruksgatan 3C, SE - 531 40 Lidköping

Model identifier: DSD8447A

Conoral	nraduct	naramatara
General	product	parameters:

General product parameters:				
Parameter	Value	Parameter	Value	
			Height	82
Rated capacity in standard place settings, for the eco programme	14	Dimensions in cm	Width	60
			Depth	55
EEI	31,8	Energy efficiency class	A	
Cleaning performance index	1,121	Drying performance index	1,061	
Energy consumption in kWh [per cycle], based on the eco programme using cold water fill. Actual energy consumption will depend on how the appliance is used.	0,540	Water consumption in litres [per cycle], based on the eco programme. Actual water consumption will depend on how the appliance is used and on the hardness of the water.	9,4	
Programme duration (h:min)	4:35	Туре	Built-in	
Airborne acoustical noise emissions (dB(A) re 1 pW)	40	Airborne acoustical noise emission class	В	
Off-mode (W)	-	Standby mode (W)	0,49	
Delay start (W)	3,99	Networked standby (W)	-	
Minimum duration of the guarantee of	offered by the ma	nufacturer: 24 months		
Additional information:				