



Effectively removes odours for a fresh kitchen

The 500 ExtractionTech Plus cooker hood offers fast and thorough kitchen air cleaning with its powerful motor. Effortlessly eliminate even the strongest cooking odours for a completely fresh environment every time you cook.

Product Benefits & Features



ExtractionTech Plus. High-performance odour extraction

ExtractionTech Plus ensures your kitchen stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.



Light up your cooking with Pure Illumination

Our Pure Illumination provides intense and durable lighting for full visibility while cooking. The energy-efficient LED lights illuminate your entire cooking surface, making it easy to see every detail of your meal preparation.



Grease filter with reliable performance

Experience reliable grease filtering. Designed for convenience, it can be easily cleaned by hand or in the dishwasher, ensuring your kitchen stays fresh and your hood performs at its best.

- Installation type: Chimney, width 90 cm
- Air extraction capacity (high/low): 600 / 290 m³/h
- Noise min/max/intensive: 49/66/dB(A)
- Number of speeds: 3
- Cooker hood lamps type and number: LED spotlight, 2
- Perimeter extraction for lower energy consumption and noise levels
- Push button controls with 3 speeds
- Return flap
- Grease filter type and number: Aluminium mesh, 1
- Extraction mode or recirculation possible, charcoal filter included.
- Recirculation capacity, man/max/intensive: 260/490/ m³/h

Product Specification

Main colour	Black	Recirculation Max, m³/h-2ndGen	490
Speeds	3	Recirc. sound power min, dB(A)	57
Control type	Mechanical push buttons	Recirc. sound power max, dB(A)	72
Lamp type	LED spotlight	Product Number Code	942 051 544
Energy efficiency class Hood	C	Bar code	7333394103648
Hoods_Capacity_Min_Max_Intensive_m3h	290/600/-	Net weight, kg	16.2
Hoods_Noiselevel_Min_Max_Intensive_dB	49/66/-	Gross weight, kg	21.1
Grease filter efficiency class	D	Dimensions HxWxD in mm	1260x898x152
Min dist.from cook.top electric, cm	50	Installation	Chimney
Min dist.from cook.top gas, cm	65	Grease filter, n° of	1
Annual Energy consumption, KWh/annum	106.7	Filter Type	Aluminium mesh
Size, cm	90	Cord length, m	1.2
Recirculatory	Yes	Air outlet, mm	150
External evacuation	Yes	Volt, V	220-240
Light temperature, K	3000	OdourClean Standard Carbon filter	2;Included
Lamp, n° of	2	OdourClean Standard Carbon filter type	ECFB02ST
Fluid dynamic efficiency class	D	OdourClean Plus Carbon filter type	MCFB52PL
Fluid dynamic efficiency index	16.9	OdourClean Pro Carbon filter type	NO
Grease filter efficiency index	65.1		
Lighting efficiency class	A		
Lighting efficiency index	47.2		
Recirculation Min, m³/h-2ndGen	260		

