


**Effectively removes odours for a fresh kitchen**

The 500 ExtractionTech Plus cooker hood offers fast and thorough kitchen air cleaning with its powerful motor. Effortlessly eliminate even the strongest cooking odours for a completely fresh environment every time you cook.

**Product Benefits & Features**

**ExtractionTech Plus. High-performance odour extraction**

ExtractionTech Plus ensures your kitchen stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.


**Light up your cooking with Pure Illumination**

Our Pure Illumination provides intense and durable lighting for full visibility while cooking. The energy-efficient LED lights illuminate your entire cooking surface, making it easy to see every detail of your meal preparation.


**Grease filter with reliable performance**

Experience reliable grease filtering. Designed for convenience, it can be easily cleaned by hand or in the dishwasher, ensuring your kitchen stays fresh and your hood performs at its best.

- Installation type: Chimney, width 60 cm
- Air extraction capacity (high/low): 600 / 290 m³/h
- Noise min/max/intensive: 49/66/dB(A)
- Number of speeds: 3
- Cooker hood lamps type and number: LED spotlight, 2
- Perimeter extraction for lower energy consumption and noise levels
- Push button controls with 3 speeds
- Return flap
- Grease filter type and number: Aluminium mesh, 1
- Extraction mode or recirculation possible, charcoal filter included.
- Recirculation capacity, man/max/intensive: 260/490/ m³/h

Product Specification

Main colour	Black	Recirculation Max, m³/h-2ndGen	490
Speeds	3	Recirc. sound power min, dB(A)	57
Control type	Mechanical push buttons	Recirc. sound power max, dB(A)	72
Lamp type	LED spotlight	Product Number Code	942 051 545
Energy efficiency class Hood	C	Bar code	7333394103617
Hoods_Capacity_Min_Max_Intensive_m3h	290/600/-	Net weight, kg	14
Hoods_Noiselevel_Min_Max_Intensive_dB	49/66/-	Gross weight, kg	18
Grease filter efficiency class	D	Dimensions HxWxD in mm	1260x598x176
Min dist.from cook.top electric, cm	50	Installation	Chimney
Min dist.from cook.top gas, cm	65	Grease filter, n° of	1
Annual Energy consumption, KWh/annum	106.7	Filter Type	Aluminium mesh
Size, cm	60	Cord length, m	1.2
Recirculatory	Yes	Air outlet, mm	150
External evacuation	Yes	Volt, V	200
Light temperature, K	3000	OdourClean Standard Carbon filter	Included
Lamp, n° of	2	OdourClean Standard Carbon filter type	ECFB02ST
Fluid dynamic efficiency class	D	OdourClean Plus Carbon filter type	MCFB52PL
Fluid dynamic efficiency index	16.9	OdourClean Pro Carbon filter type	NO
Grease filter efficiency index	65.1		
Lighting efficiency class	A		
Lighting efficiency index	51.7		
Recirculation Min, m³/h-2ndGen	260		

