


EEA27200L





Natural drying with fresh air

Our 300 AirDry Dishwasher finishes each cycle with a breath of fresh air, performing 3x better than closed-door systems. The door opens automatically during the drying phase using fresh air to get plates and cutlery completely dry.

Product Benefits & Features



3x better drying with AirDry

The new AirDry technology uses natural airflow to finish drying, for up to 3x better performance compared to closed-door systems. The door opens 10 cm towards the end of the cycle, letting air circulate for superb drying results.



AutoSense, the smart selection

Enjoy a fully-customised dishwasher cycle, every time, with the AutoSense programme. Smart sensors automatically adjust the time, temperature and water usage depending on how much cleaning each load needs. It's efficient washing for the best results.

Easy installation, PerfectFit



With PerfectFit Sliding Hinges, it's never been easier to install your new dishwasher. The hinges accommodate all niche machine heights and even remove the need to cut the plinth. You can be confident that your machine will fit into your kitchen perfectly.

- Auto Off function
- · Panel with symbols
- · Touch control for programs and functions selection
- Drying system: AirDry Technology
- Cutlery basket
- Water sensor detects the level of dirt and adjusts water consumption
- · Indications for salt and rinse aid
- · Ceiling sprayarm
- · Height adjustable upper basket, even when fully loaded
- Upper basket with Foldable cup shelves
- Lower basket with Fixed tines
- Dishwasher programmes: 90 Minutes, AUTO Sense, ECO, Machine care, Quick Cycles, Rinse & Hold
- Delay Start



EEA27200L

Product Specification			
Installation	FI	Water consumption / cycle IE20	9.9
Rated capacity psE20	13	Hinges	Sliding
Energy efficiency class, legal (E20)	E	Connected load, W	1950
Airborne acoustical noise emissions, dBA re 1 pW	46	Cord length, m	15
Door colour	None	Outlet hose length, cm	150
XXL-Tub	No	Required fuse (A)	10
Dimensions_Dishwasher_FSBU_DK	820-900x600x550	Inlet hose length, cm	150
		Inlet hose type	Aqua control
Number of programs	6	Anti-flood device	Floating switch
Number of temperatures	2	Water supply	Cold or Hot
Dimensions HxWxD in mm	818x596x550	Upper spray arm	Standard spray arm
Airborne acoustical noise emission class	С	Lower spray arm	Standard
Depth open door	1200	Options	XtraPower
Nordic_DW_CutleryType	Cutlery basket	Feet/Wheels	2 adj feet + 1 front adj rear foot (adj 0 to 8cm)
Nordic_DW_QuickSelect	Level 1	Installation in height	None
Nordic_DW_GlassCare2G	No	Nordic_DW_DoorPanelHeight	645-776
Interior light	No	Nordic_DW_DoorPanelWeight	2-10
Nordic_DW_DoorFitKit	No	Indicator program	LED
Cleaning performance index3 digitE20	1.121	Installation type	Built_In
Drying performance index 3 digitE20	1.061	Net weight, kg	34
Weighted average energy	94	Bar code	7332543798360
consumption / 100 cycles, kWh (E20)	34	- 311 7777	
		Product Number Code	911 535 282

